


GAMA SPLIT PARED 1X1

MODELO			ON/OFF				INVERTER	
								
			09KBtu	12KBtu	18KBtu	24KBtu	12KBtu	24KBtu
			ASW-H09 A4/EZR1-C	ASW-H12 B4/EZR1-C	ASW-H18 B4/EZR1X-C	ASW-H24 B4/EZR1-C	ASW-H12 A4/S*R1DI	ASW-H24 A4/SFR1DI
CAPACIDAD	FRIO	Btu	9.000	12.000	18.000	24.000	12.000	
		W	2.700	3.550	5.300	7.000	3.550	6.500
		Kcal./H	2.322	3.053	4.558	6.020	3.053	5.590
	CALOR	Btu	9.566	12.437	19.180	24.490	12.437	
		W	2.800	3.650	5.620	7300	3.800	6.600
		Kcal./H	2.408	3.139	4.833	6.278	3.268	5.676
EER (FRIO)		W/W	3,21	3,21	3,20	3,01	3,37	3,28
COP (CALOR)		W/W	3,61	3,61	3,61	3,21	3,61	3,62
CONSUMO		W	776	1.011	1.557	2.274	1053(380~1300) 1823(550~2700)	
INTENSIDAD ABSORBIDA		Amp	3,37	4,39	6,76	9,88	5.32(1.8~7.0)	8.0(3.4-11.7)
REFRIGERANTE		Gas	R-410				R-410	
FUENTE DE ALIMENTACION		V/Hz/Ph	220-240/50/1				220-240/50/1	
CARGA DEL REFRIGERANTE		Grs.	680	850	1250	1630	1100	1750
VOLUMEN DE AIRE		m³/h	400	520	850	950	580	850
NIVEL SONORO	Ud. Interior	dB	36	37	38	42	35	45
	Ud. Exterior	dB	50	52	54	55	53	53
PESO NETO	Ud. Interior	Kg	9	9	15	15	11	15
	Ud. Exterior	Kg	29	34	44	53	36	52
DIMENSIONES UNIDAD INTERIOR	NETO	Ancho	745	745	1095	1095	880	1095
		Alto	250	250	312	312	286	312
		Fondo	210	210	205	205	203	215
	BRUTO (Packing)	Ancho	800	800	1175	1160	950	1175
		Alto	320	320	375	375	350	375
		Fondo	280	280	275	275	270	275
DIMENSIONES UNIDAD EXTERIOR	NETO	Ancho	760	760	800	800	760	800
		Alto	540	540	590	690	540	690
		Fondo	260	260	300	300	260	300
	BRUTO (Packing)	Ancho	880	880	940	940	880	940
		Alto	600	600	650	650	600	750
		Fondo	370	370	420	420	370	420
MARCA DEL COMPRESOR			GMCC	GMCC	HITACHI	GMCC	GMCC	SANYO
CAPACIDAD CONTENEDOR 20/40/40HC			265	265	180	170	255	170